

POREX® Porous PTFE Materials

Material Data Sheet



PMP32

PARAMETERS	VALUE	UNIT OF MEASUREMENT
PMAX % PENETRATION	0.007	ASTM F2638
GURLEY AIR FLOW (NOMINAL)	5.8	seconds/100cc
THICKNESS	0.26	mm ± 0.04

ADDITIONAL INFORMATION

ADDITIONAL INFORMATION:

- Can be supplied in format of:
 - Rolls (10mm-330mm width) on 75mm core
 - Sheets
 - Discs
- Assembly suggestions:
 - Ultrasonic welding
 - Thermal welding
 - Pressure Sensitive Adhesive
- Sterilisation Methods:
 - Steam
 - EtO
- Material can be ink printed
- Raw material is compliant with:
 - USP 28, NF 23, 2005, for USP Class VI Plastics at 70°C
 - FDA 21CFR 177.1550



This standard sample is for evaluation of form, fit, and function to determine product specification requirements for custom products. Please reference the values in our data sheet for specification guidelines of standard products. For medical or pharmaceutical applications please contact us to discuss material and regulatory requirements.



www.porex.com
800.241.0195

Porex Corporation
500 Bohannon Road,
Fairburn, GA 30213
USA

info@porex.com
T. +1 770 964 1421
F. +1 770 969 0954

Porex Technologies GmbH
Strangenhäuschen 30,
52070 Aachen,
Germany

info@porex.de
T. +49 241 910525-0
F. +49 241 910525-16

Porex Technologies Sdn Bhd
Lot P.T. 74, Jalan Hulu Tinggi
26/6, Seksyen 26, Sektor A Hicom
Industrial Park, 40400 Shah Alam,
Selangor, Malaysia

info@porex.com.my
T. +603 5191 3308
F. +603 5192 3308

Porex Technologies Ltd.
Merlin House, Alness Point
Business Park Alness,
Ross-shire IV17 OUP,
Scotland, UK

infoPTFE@porex.com
T. +44 1349 884060
F. +44 1349 884076